

M71V2

Wireless Terminal



Designed for comfort and ease of use

The AML M71V2 wireless handheld terminal provides comfort and ease of use for everyday, scan-intensive data capture applications. Its lightweight, contoured design supports comfortable, one-handed operation over extended periods of use. The graphical 160 x 160 backlit LCD with multi-font capability is easy to read, even in dimly lit environments. The spacious LCD screen accommodates the display of large amounts of information, minimizing the need for screen scrolling.

Designed for operational flexibility across a wide range of data collection applications, the M71V2 features an easy-to-use 55-key alphanumeric keypad, multiple integrated scanner options (both 1D and 2D), RS-232 and infrared communication ports. Accessories include single and four position communications/charging cradles, a four position battery charger, a vehicle mount charger, a removable pistol grip with trigger and multiple holsters.

There are many available charging accessories for the M71V2, including a single slot terminal charger, a four-position terminal charger, and four-position battery charger.



Features

Benefits

Rugged, ergonomic design	Supports comfortable, one-handed operation over extended periods of use. Holds up in industrial environments.
Samsung® ARM9 processor	Rapid processing power
Integrated IEEE 802.11b radio with up to 11Mbps throughput	Industry standard WLAN radio technology for real-time, high-rate data transfer
32MB RAM/16MB ROM	Ample storage capacity, even for the most information-intensive applications
WEP and WPA/WPA2 security	High-level security protection. Includes EAP-TLS, EAP-PEAP, EAP-TTLS and PSK-TKIP
Graphical 160 x 160 backlit LCD display with multi-font capability	Easy to read, even in dimly lit environments
55-key alphanumeric keypad	Maximizes data entry across a wide range of data collection applications
Rechargeable, high capacity 2200 mAh Lithium-Ion battery	Enhanced power management for eight-hour work shifts without recharging
Open source, embedded Linux® architecture	Highly reliable system performance
IrDA Communication Port	Allows communication to peripheral devices

Physical Specs

Dimensions	225 mm L x 89 mm W x 57 mm D; 8.875" L x 3.5" W x 2.25" D
Weight	18.5 oz / 525 g
Drop Specifications	5 ft. (1.5m) drop to concrete
Display	Graphical 160 x 160 backlit EL LCD with multi-font capability
Battery	Rechargeable 2200 mAh Lithium-Ion
Keypad	55-key alphanumeric
Integrated Barcode Scanners (optional)	Standard Laser; Long Range Laser; Advanced Long Range Laser; 2-Dimensional Imager

Performance Specs

CPU	Samsung® S3C2410 32-bit ARM9 @ 202 MHz with Advanced Microcontroller Bus Architecture (AMBA)
Operating System	Open source, embedded Linux®
Memory	32MB RAM/16MB ROM
Development Environment	Application development using GNU C Compiler
Communications	IrDA; RS-232

Environmental Specs

Operating Temp	-10° to 50° C / 14° to 122° F
Storage Temp	-25° to 50° C / -13° to 122° F
Humidity	5% to 90% RH, non-condensing
Electrostatic Discharge (EDS)	15kVDC air; 4kVDC contact
Sealing	IP51 (dust, drip water proof)

Regulatory Specs

Certifications	FCC Part 15 Class A
Laser Safety	CDRH Class II, IEC Class 2



Software Specs

Terminal Emulation	VT100/VT220/TN5250 Clients
Built-In Functions	TELNET Server; FTP Server; HTTP Server; Web Server; Web Browser

Wireless Communications

Radio	IEEE 802.11b Standard
Frequency	2.4 GHz
Output Power	17dBm (40 mW)
Security	Support for WEP & WPA/WPA2 encryption & authentication (EAP-PEAP, EAP-TLS, EAP-TTLS, & PSK-TKIP)
Antenna	Internal Diversity

Peripherals & Accessories (optional)

Cradles	Single slot communication & charging cradle; Four slot terminal charger; Four slot battery charger
Vehicle	Vehicle mount terminal charger; Vehicle mount cradle (non-charging)
Pistol Grip	Removable pistol grip with trigger
Holster	Two styles of functional holsters w/ adjustable belts

Maintenance & Support

Standard Warranty	One year standard warranty agreement
Optional	Extended Warranty Plus (3 years); Extended Warranty (3 years); CARE Plan Extended Warranty (3 years)

Linux® is the registered trademark of Linus Torvalds in the U.S. and other countries.

Specifications are subject to change without notice. All names and products are the trademarks or registered trademarks of their respective organizations.



AML Corporate Headquarters Local: **817-571-9015**
2190 Regal Parkway Fax: **817-571-6176**
Euless, Texas 76040 Visit us online at: www.amltd.com

Sales & Customer Service
Tel: **800-648-4452**
Fax: **817-685-6232**
Email: sales@amltd.com

Technical Support
Tel: **877-842-3990**
Fax: **817-685-6232**
Email: support@amltd.com



© 2010 American Microsystems, Ltd.