

# MT7570

## Vehicle Mount Computer



### Robust Mobile Performance

The AML MT7570 vehicle mount computer combines a rugged IP65 sealed metal construction with robust mobile computing capabilities to provide years of reliable service in harsh industrial environments. The MT7570 mounts easily to industrial vehicles such as forklift trucks and delivers the tools necessary to keep information flowing in real-time receiving, put-away, picking and shipping applications.

Engineered for computing flexibility, the AML MT7570 vehicle mount computer is available with either open-source embedded Linux® or Windows® XP Embedded. Both operating systems include terminal emulation clients (VT100/220, TN5250, TN3270), web browser(s), Microsoft® Windows Terminal Services (RDP), and VoIP (Skype®) client at no additional cost – maximizing the value of your investment.

## Applications

Inventory  
Shipping/Receiving

Factory Floor  
Management

Stock Control  
Asset Tracking



### Features

Microsoft® Windows XPe or Linux® operating system

Rugged, heavy-duty metal enclosure

Bright SVGA Color 12.1" TFT touch screen display

Integrated 802.11b/g WLAN radio with internal antenna

Internal DC power converter

Built-in clients and VoIP client – at no additional charge

WEP, WPA/WPA2 and 802.11x security

Audio, full USB and RS232 serial connections (Optional: Bluetooth® WPAN)

Mounting hardware included

### Benefits

Computing flexibility – choose the operating system that best meets your business and IT needs.

IP65 sealed construction withstands harsh mobile environments. Total protection from dust and water sprayed from any direction.

Easy to read in outdoor and indoor operations. Backlit with high visibility 160° viewing angle.

Industry standard radio technology for easy connectivity to existing wireless LANs.

Accommodates 12 to 36VDC or 36 to 75VDC (depending on configuration).

Ships standard with terminal emulators, modern service protocols, web browser(s), utilities and VoIP (Skype®) client – maximizing the value of your investment.

The latest in wireless security protocols ensure protection of sensitive data.

Supports flexible connectivity with peripheral devices.

Ships complete with all the hardware necessary to securely mount the MT7570 to industrial vehicles.

## Physical Specs

<b>Dimensions</b>	44 cm L x 40 cm W x 6.5 cm D; 15.625" L x 12.75" W x 2.63" D (w/ mounting arm)
<b>Weight</b>	14.3 lbs / 6.45 kg (with mounting arm)
<b>Display</b>	Industrial 12.1 inch SVGA 800 x 600, 18-bit Color – Liquid Crystal Display; Super hi-bright, 160 degree viewing angle, backlight, & antiglare
<b>Touch Screen</b>	12.1 inch resistive touch panel overlay
<b>Keypad</b>	Virtual on-screen keypad; Optional USB full QWERTY compact keyboard w/ integrated touchpad and IP54 spill and dust resistant key field
<b>Power Supply</b>	Internal isolated power supply w/ power cable for vehicle attachment; Accepts 12 to 36VDC input or 36 to 75VDC input, depending on configuration
<b>Internal UPS Battery</b>	Optional 12.6V Lithium-Polymer battery ensures stable service in case of power failure for up to 30 minutes
<b>I/O Ports</b>	Two full USB 2.0 high-speed ports (1 x USB 2.0 w/ optional Bluetooth® module); RS-232C serial port with 5V Pin 9
<b>Audio</b>	Amplified headphone jack; non-amplified line-out jack; line input; microphone jack; two internal amplified speakers
<b>Housing</b>	Heavy-duty, steel enclosure
<b>Mounting</b>	Includes mounting hardware

## Performance Specs

<b>CPU</b>	AMD Geode GX533 @ 400 MHz
<b>Operating System</b>	AML Debian/GNU 4.0 Platform Linux® Kernel 2.6.18; Windows® XP Embedded
<b>Architecture</b>	32-bit x 86
<b>Memory (RAM/ROM)</b>	<b>Linux® version:</b> 128 MB SDRAM/512MB Internal Flash; <b>Windows® XPe:</b> 384 MB SDRAM/1 GB Internal Flash

## Environmental Specs

<b>Operating Temp</b>	-20° to 50° C / -4° to 122° F
<b>Storage Temp</b>	-30° to 60° C / -22° to 140° F
<b>Humidity</b>	5% to 95% RH, non-condensing
<b>Sealing</b>	IP65 standards for protection against dust and water sprayed from any direction

## Regulatory Specs

<b>Certifications</b>	FCC Part 15, IEC Class A
-----------------------	--------------------------



## Software Specs

<b>Client Software</b>	<b>Linux® version:</b> VT100, VT220, TN5250, TN3270, Web Browser, Windows® Terminal Services (RDP), and Virtual Network Computing (VNC); <b>Windows® XPe version:</b> VT100, VT220, TN5250, TN3270, Internet Explorer® Web Browser, and Windows® Terminal Services (RDP)
<b>Utilities</b>	Calculator, text editor, virtual keyboard
<b>VoIP</b>	Skype® client

## Wireless Communications WLAN

<b>Radio</b>	IEEE 802.11b/g
<b>Frequency</b>	2.4 GHz
<b>Output Power</b>	15 dBm (±3 dB) @ 54 Mbps; 19 dBm (±3 dB) @ 11 Mbps
<b>Security</b>	None; 64/128 Bit WEP; WPA/WPA2 Personal (PSK); WPA/WPA2 Enterprise (EAP); 802.1x supplicants
<b>Antenna</b>	Internal

## Wireless Communications WPAN (optional)

<b>Radio</b>	Bluetooth® v1.2 and v1.1 compliant
<b>Range</b>	Up to 160 feet (50 meters)
<b>Data Rate</b>	Up to 2.1 Mbps

## Accessories (optional)

<b>Keyboard Kit</b>	USB keyboard with shelf
---------------------	-------------------------



## Maintenance & Support

<b>Standard Warranty</b>	One year standard warranty agreement
<b>Optional</b>	Extended Warranty Plus (3 years); Extended Warranty (3 years); CARE Plan Extended Warranty (3 years)

Linux® is the registered trademark of Linus Torvalds in the U.S. and other countries.

Windows is a registered trademark of Microsoft Corporation in the United States and other countries.

Specifications are subject to change without notice. All names and products are the trademarks or registered trademarks of their respective organizations.



**AML Corporate Headquarters** Local: 817-571-9015  
2190 Regal Parkway Fax: 817-571-6176  
Euless, Texas 76040 Visit us online at: [www.amltd.com](http://www.amltd.com)

**Sales & Customer Service**  
Tel: 800-648-4452  
Fax: 817-685-6232  
Email: [sales@amltd.com](mailto:sales@amltd.com)

**Technical Support**  
Tel: 877-842-3990  
Fax: 817-685-6232  
Email: [support@amltd.com](mailto:support@amltd.com)



© 2010 American Microsystems, Ltd.